



PRODUCT CATALOGUE



 1800-103-5841

 www.jalelectricals.com

 jalelectricals@yahoo.co.in | info@jalelectricals.com

RO WATER PURIFIERS

RO HEALTH, RO CARE

YOUR WATER, OUR PRIORITY

T-1 RO Water Purifier

15 LITRES/HOUR

PURIFICATION - 6 STAGES

PP + SEDIMENT + GAC + ANTISCALENT +
MEMBRANE + POST CARBON

MAXIMUM CAPACITY	60 LITRES PER DAY	INLET WATER PRESSURE	30 PSI
STORAGE CAPACITY	9 LITRES	DIMENSION	425mm x 257mm x 342mm
RO MEMBRANE	80 GPD	NET WEIGHT	11 KG
BOOSTER PUMP	100 GPD	OPTIONAL FILTER	UV/UF/TDS CNTROLLER/ALKALINE/COPPER/B12



T-2 RO Water Purifier

15 LITRES/HOUR

PURIFICATION - 7 STAGES

PP + SEI T + GAC + ANTISCALENT + MEMBRANE +
TDS CO .LER + POST CARBON

MAXIMUM CAPACITY	60 LITRES PER DAY	INLET WATER PRESSURE	30 PSI
STORAGE CAPACITY	15 LITRES	DIMENSION	480mm x 250mm x 300 mm
RO MEMBRANE	80 GPD	NET WEIGHT	7 KG
BOOSTER PUMP	100 GPD	OPTIONAL FILTER	UV/UF/ALKALINE/COPPER/B12

T-3 RO Water Purifier

15 LITRES/HOUR

PURIFICATION - 9 STAGES

PP + SEDIMENT + GAC + ANTISCALENT +
MEMBRANE + UF + TDS CONTROLLER + ALKALINE CANDLE

MAXIMUM CAPACITY	60 LITRES PER DAY	INLET WATER PRESSURE	30 PSI
STORAGE CAPACITY	12 LITRES	DIMENSION	415mm x 265mm x 524mm
RO MEMBRANE	80 GPD	NET WEIGHT	10 KG
BOOSTER PUMP	100 GPD	OPTIONAL FILTER	COPPER/B12



S-1/S-2 RO Water Purifier

15 LITRES/HOUR | 25 LITRES/HOUR

PURIFICATION - 6 STAGES

PP + SEDIMENT + GAC + ANTISCALENT +
MEMBRANE + TDS CONTROLLER + POST CARBON

MAXIMUM CAPACITY	100 LITRES PER DAY	INLET WATER PRESSURE	30 PSI
STORAGE CAPACITY	15 LITRES 25 LITRES	DIMENSION	420mm x 280mm x 510mm
RO MEMBRANE	80 GPD (1 PC) 80 GPD (2 PCS)	NET WEIGHT	17 KG
BOOSTER PUMP	100 GPD (1 PC) 150 GPD (1 PC)	OPTIONAL FILTER	UV/UF/ALKALINE/COPPER/B12

S-3 RO Water Purifier

50 LITRES/HOUR

PURIFICATION - 9 STAGES

PP + SEDIMENT + GAC + ANTISCALENT +
MEMBRANE + TDS CONTROLLER + UF + ALKALINE

MAXIMUM CAPACITY	200 LITRES PER DAY	INLET WATER PRESSURE	30 PSI
STORAGE CAPACITY	50 LITRES	DIMENSION	535mm x 345mm x 775 mm
RO MEMBRANE	300 GPD (2 PCS)	NET WEIGHT	24 KG
BOOSTER PUMP	300 GPD (2 PCS)	OPTIONAL FILTER	UV/COPPER



200-1000 LPH R.O. SYSTEM



NAME	RO 250	RO 500	RO 1000
OUTPUT WATER CAPACITY (LITRE/HOUR)	200	400	1000
INPUT WATER TDS	2000	2000	2000
RECOVERY AT 27 DEGREE CENTIGRADE	40-50%	40-50%	40-50%
ARENSIC AND FLORIDE REMOVAL CAPACITY	NO	NO	NO
THIN FILM COMPOSITE MEMBRANE	YES	YES	YES
RAW WATER/PUMP	YES	YES	YES
PRE FILTER VESSELS	YES	YES	YES
MICRO FILTER	YES	YES	YES
MEMBRANE HOUSING	YES	YES	YES
AUTO CUT	YES	YES	YES
NO. OF CANDLES	2	2	2

WATER SOFTENER

NAME	JWS 3B	JWS 6B	JWS 9B	JWS 14B	JWS 20B	JWS 30B	JWS 40B	JWS 50B
VESSEL SIZE	13X54	16X65	21X62	24X72	30X72	35X72	42X72	48X72
FLOW RATE (M ³ /H)								
MINIMUM	0.3	0.6	0.9	1.4	2.0	3.0	4.6	5.0
MAXIMUM	3.0	6.0	9.0	10.0	20.0	30.0	40.0	50.0
WORKING PRESSURE (KG/CM ²)								
MINIMUM	2	2	2	2	2	2	2	2
MAXIMUM	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
*OUTPUT/REGENERATION (M ³) (200 PPM TOTAL HARDNESS AS CaCO ₃)	28	50	84	130	168	224	308	406
TREATED WATER HARDNESS PPM CaCO ₃	<5	<5	<5	<5	<5	<5	<5	<5
SALT/REGENERATION (KG)	16	24	48	72	96	128	176	232
INLET/OUTLET/DRAIN CONNECTION (PVC SOCKET UNION)								
INLET (MM)	50	50	50	50	63	90	90	110
OUTLET (MM)	50	50	50	50	63	90	90	110
DRAIN (MM)	50	50	50	50	63	90	90	110
DIMENSIONS								
VESSEL DIA (MM)	335	400	552	610	770	927	1074	1226
VESSEL HEIGHT (MM)	1388	1671	1735	2336	2336	2336	2336	2336
RESIN QUANTITY (LITERS)	100	175	300	450	600	800	1100	1450

AUTOMATIC



MANUAL



WATER COOLER & DISPENSERS

Usha's range of Water Coolers is designed to deliver like no other! While their efficient design and rugged body gives them a long life, their low power consumption and fast cooling gives you a best-in-class experience, every time.

USHA


TABLE TOP
WATER DISPENSER




FLOOR STANDING
WATER DISPENSER



WATER COOLER
(SS)



COMPACT & SLEEK
DESIGN TO FIT INTO
ANY SETTING



DESIGNED FOR
EFFICIENT COOLING
EVEN IN HOT
INDIAN CONDITIONS



SAFETY MESH
FOR RODENT
CONTROL



CHILD LOCK
ON HOT WATER
FAUCETS



CFC FREE
ECO-FRIENDLY
R134A REFRIGERANT

POLYPHOSPHATE WATER CONDITIONER



Faucets



Shower
Heads



Shower
Panels



Bathtubs
& Jacuzzi



Water
Geysers



RO
Purifiers



Washing
Machine



Dishwasher



NO SALT REQUIRED

BRING HOME SALT-FREE WATER TREATMENT PLANT

NO ELECTRICITY REQUIRED



NO LONGER NEED FOR CONSISTENT ELECTRICITY FLOW



NO WATER WASTAGE

ENHANCE WATER QUALITY BY MINIMISING WATER WASTE

EASY INSTALLATION



FUSS-FREE DEPLOYMENT WITH HIGH-QUALITY INSTALLATION

HYDRO PRESSURE BOOSTER PUMPS



FEATURES AND BENEFITS

- ▶ NSF STANDARD 61, CE/PED, WRAS, ACS, ISO:9001
- ▶ GOST, EVRAZES APPROVED PRESSURE TANK
- ▶ EASY INSTALLATION
- ▶ RELIABLE AND USER FRIENDLY OPERATION
- ▶ ADJUSTABLE PRESSURE
- ▶ RELIABLE CONSTANT PRESSURE WATER SUPPLY
- ▶ TWO PART POLYURETHANE, EPOXY PRIMED PAINT FINISH TANK
- ▶ LEAK FREE, O-RING SEALED AIR VALVE CAP PROVIDED ON TANK
- ▶ CORROSION RESISTANT
- ▶ GOOD AIR HANDLING
- ▶ RELIABLE & ROBUST CONSTRUCTION
- ▶ LOW NOISE LEVEL
- ▶ MAINTENANCE FREE
- ▶ BUILT-IN MOTO PROTECTION

www.jalelectricals.com

✉ jalelectricals@yahoo.co.in | info@jalelectricals.com

☎ Toll Free: 1800-103-5841



407, Vedanta, Opp. Usmanpura Garden, Near Hotel Fortune Landmark, Usmanpura, Ahmedabad - 380013

OUR PRESTIGIOUS CLIENTS



OUR CORPORATE CLIENTS



OUR REAL ESTATE CLIENTS



TOLL FREE: 1800-103-5841

www.jalelectricals.com

jalelectricals@yahoo.co.in | info@jalelectricals.com